## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 30 June 2005 (30.06.2005)

**PCT** 

## (10) International Publication Number WO 2005/058615 A1

- (51) International Patent Classification<sup>7</sup>: B60C 1/00, C08K 5/544, 5/548, C08L 19/00, 21/00, 23/16
- (21) International Application Number:

PCT/EP2003/014181

(22) International Filing Date:

10 December 2003 (10.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): PIRELLI & C. S.p.A. [IT/IT]; Via Gaetano Negri, 10, I-20123 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): TIRELLI, Diego [IT/IT]; c/o Pirelli Labs S.p.A., Viale Sarca, 222, I-20126 Milano (IT). GALBUSERA, Michele [IT/IT]; c/o Pirelli Labs S.p.A., Viale Sarca, 222, I-20126 Milano (IT). RESMINI, Emiliano [IT/IT]; c/o Pirelli Labs S.p.A., Viale Sarca, 222, I-20126 Milano (IT). SERRA, Antonio [IT/IT]; Pirelli Pneumatici S.p.A., Viale Sarca, 222, I-20126 Milano (IT).

- (74) Agents: BOTTERO, Claudio et al.; Porta, Checcacci & Associati S.p.A., Via Trebbia, 20, I-20135 Milano (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CROSSLINKABLE ELASTOMERIC COMPOSITION AND TIRE FOR VEHICLE WHEELS COMPRISING THE SAME

(57) Abstract: Crosslinkable elastomeric composition comprising: at least one vulcanized rubber in a subdivided form surface treated with at least one silane coupling agent; at least one diene elastomeric polymer; at least one sulfur-based vulcanizing agent. Said crosslinkable elastomeric composition is advantageously used in the production of crosslinked manufactured products, in particular in the production of tires for vehicle wheels.



2005/05861